



**CECHY PRODUKTU**

Kąt wierzchołkowy 118° standardowy. Szlifowane krawędzie. Materiał – stal szybko tnąca, uszlachetniona. Pakowane i sprzedawane w papierowej kopercie/pudełku: wymiary 0.8 - 8.0 mm po 10 szt.; wymiary 8.5 - 13.0 mm po 5 szt.



KOD	Ø [MM]	L CZĘŚCI ROB. [MM]	L CAŁK. [MM]	
76808	0,8	10	30	10/100/3000
76810	1	12	34	10/100/3000
76815	1,5	20	43	10/100/3000
76820	2	24	49	10/100/3000
76825	2,5	30	57	10/100/3000
76830	3	33	61	10/100/3000
76832	3,2	36	65	10/100/2000
76835	3,5	39	70	10/100/2000
76840	4	43	75	10/100/2000
76841	4,1	43	75	10/100/2000
76842	4,2	43	75	10/100/2000
76845	4,5	47	80	10/100/2000
76848	4,8	52	86	10/100/1000
76850	5	52	86	10/100/1000
76851	5,1	52	86	10/100/1000
76852	5,2	52	86	10/100/1000
76855	5,5	57	93	10/100/1000



## CECHY PRODUKTU

Kąt wierzchołkowy 118° standardowy. Szlifowane krawędzie. Materiał – stal szybko tnąca, uszlachetniona. Pakowane i sprzedawane w papierowej kopercie/pudełku: wymiary 0.8 - 8.0 mm po 10 szt.; wymiary 8.5 - 13.0 mm po 5 szt.



KOD	Ø [MM]	L CZĘŚCI ROB. [MM]	L CAŁK. [MM]	
76860	6	57	93	10/50/500
76865	6,5	63	101	10/50/500
76870	7	69	109	10/50/500
76875	7,5	69	109	10/50/500
76880	8	75	117	10/50/500
76885	8,5	75	117	5/50/300
76890	9	81	125	5/50/300
76895	9,5	81	125	5/50/300
76900	10	87	133	5/50/300
76905	10,5	87	133	5/50/300
76910	11	94	142	5/50/200
76915	11,5	94	142	5/50/200
76920	12	101	151	5/50/200
76925	12,5	101	151	5/50/200
76930	13	101	151	5/50/200